

# SAFETY DATA SHEET

SDS No: 0005

Section 1. Product and Company Identification

Product Name: DigiMark Osi™ - Color

Trade Name: Film-stamped Impact Modified Acrylic

Recommended Use: Signage, Other

Restrictions on Use: None

Manufacture: Rowmark In Case of Emergency: Call: Med

5409 Hamlet Drive

Findlay, OH 45840 Information:

II: Medical: 911

Poison Control: 800-589-3897

Call: 1-877-ROWMARK

Email: techhelp@rowmark.com

### Section 2. Hazard Identification

GHS Classification: Not Classified GHS Label Elements: Not Applicable

### **GHS Rating**

Health	5
Flammability	4
Instability	5

# **NEW GHS Hazard Categories**

Category 1 = Severe Hazard

Category 2 = Serious Hazard

Category 3 = Moderate Hazard

Category 4 = Slight Hazard

Category 5 = Minimal Hazard

## Section 3. Composition / Information on Ingredients

Name	CAS#	% by Weight	OHSA
P (EA/MMA)	Proprietary	50-54	N
Acrylic Styrene Copolymer	Proprietary	35-50	N
Methyl methacrylate	80-62-6	< 0.5	Υ
Ethyl acrylate	140-88-5	< 0.1	Υ
Aluminium Flake	7429-90-5	1-5	
Carbon Black	1333-86-4	1-5	
Copper	7440-50-8	1-2	

The substance(s) marked with a "Y" in the OSHA column are idenfitied as hazardous chemicals according to the criteria of the OSHA Hazardous Communication Standard (29 CFR 1910.1200).

While this material is not classified as hazardous under Federal OSHA regulations, this SDS contains valuable information critical to the safe handling and proper use of this product. This SDS should be retained and available for employees and other users of this product.

The components of this product are all on the TSCA Inventory list. \* Remaining components are proprietary, non-hazardous, and/or present at amounts below reportable limits.

Section 4.	First Aid Measures		
Inhalation:	Dust and process vapors may be irritation to the nose, throat and respiratory tract. Remove to fresh air. If not		
	breathing, give artificial respiration. If breathing is difficult, give oxygen. Get Medical attention.		
Eyes:	Dust, fines and process vapors may irritate the eyes. Immediately flush eyes with water for at least 15 minutes.		
	Get medical attention.		
Skin:	Exposure to molten plastic may cause thermal burns. If molten material comes in contact with the skin, cool under		
	ice water or a running stream.		
Ingestion:	No adverse health effects expected from ingestion.		
Section 5.	Fire-Fighting Measures		

Suitable Extinguishing Methods:	Dry Chemical, Water Spray, Foam Carbon Dioximolten burning material.	de. Avoid using direct streams of water on	
Unsuitable Extinguishing Methods:	NONE known.		
Hazards During Fire-fighting:	Carbon monoxide, carbon dioxide, original mono	omer other hydrocarbon oxidation products.	
Protective Equipment:	Wear self-contained breathing apparatus and pr	otective suit.	
Section 6. Accidental Releas	e Measures		
Personal Precautions:	See Section 8 - Exposure Controls / Personal Pr	rotection.	
Environmental Precautions:	No Special environmental precautions required.		
Methods and Materials for Contai	nment and Cleaning Up		
Spill / Leak: Containment container for	of this material should not be necessary. Sweep disposal.	up or gather material and place in appropriate	
Section 7. Handling and Stor	rage		
	om heat, flame and strong oxidizing agents.		
Storage: Keep away fr	om heat, sparks, and flame. Store in cool place in	original container and protect form sunlight.	
· .	and Personal Protection		
Exposure Limits:			
1) Effects of Acute Exposure:	Inhalation of vapors may result in irritation of up	per respiratory tract	
2) Effects of Over Exposure:			
3) OSHA PEL:	US. ACGIF Thres		
	Form:	Inhalable particles	
	Time weighted average	10 mg/m3	
	Form:	Respirable particles	
	Time weighted average	3 mg/m3	
	US. OSHA Table Z-1 Limits for Air (	Contaminants (29 CFR 1910.1000)	
	Form:	Respirable fraction	
	PEL:	5 mg/m3	
	Form:	Total dust	
	PEL:	15 mg/m3	
	US. OSHA Table Z-3	(29 CFR 1910.1000)	
	Form:	Respirable fraction	
	Time weighted average	15 ppm	
	Form:	Total dust	
	Time weighted average	50 ppm	
	Time weighted average		
	Form:	Respirable fraction	
	Time weighted average	5 mg/m3	
	Form:	Total dust	
	Time weighted average	15 mg/m3	
4) Carcinogen Potential:			
Engineering Controls:			
	safe handling practices to minimize unnecessary	exposure	
	lation is adequate for storage and ordinary handling	<u> </u>	
	at points of fume generation or if dusty conditions	-	
Personal Protective Equipment:	, 5,		
	es with side shields or chemical goggles to prevent	eye contact.	
	facilities readily available where eye contact can o	-	
	loves and protective clothing to prevent skin conta		

	nd Chemical Properties	lv B	N. ( A. P. 1.1	
Appearance:	Various Colors	Vapor Pressure:	Not Applicable	
Odor:	Slightly acrylic	Vapor Density:	Not Applicable	
pH:	Not applicable	Relative Density:	1.19 g/cm3	
Melting Point / Freezing Po		Solubility (ies):	Not Applicable	
Boiling Point:	No data available	Partition Coefficient (N-Octanol		
Flash Point:	Not applicable	Auto-Ignition Temperature:	739°F (393°C)	
Evaporation Rate:	Not applicable	Decomposition Temperature:	>572°F (> 300°C)	
Flammability (solid, gas):	See GHS in section 2	Viscosity:	No data available	
Upper Explosive Limit:	Not applicable	Specific Gravity:	1.19 Water = 1 (liquid)	
Lower Explosive Limit:	Not applicable	Percent Volatile:	0%	
Section 10. Stability R	eactivity			
Reactivity:	No data available			
Chemical Stability:	Stable	Stable		
Possibility of Hazardous Re	actions: Hazardous polymeriza	Hazardous polymerization does not occur		
Conditions to Avoid:		Avoid flames, welding arcs, potential ignition sources, or other high temperature sources, prolonged contact with acids, alkalis and strong oxidizing agents		
Incompatible Materials:		None under normal conditions of use		
Hazardous Decomposition	Hazardous Decomposition Products: Carbon oxides, Acrylates, Methacrylates, Hazardous organic compounds			
Combustion Products:				
Section 11. Toxicolog	ical Information			
Irritation Effects				
Eye Irritation	on: Solid particles may ca	use transient irritation from mech	nanical abrasion.	
Skin Irritati	on: Not expected to cause	Not expected to cause skin irritation. Molten material may cause thermal burns.		
Inhalation:	Not a likely route of ex	Not a likely route of exposure. Process fumes may cause irritation.		
Ingestion:	May cause a choking l	May cause a choking hazard if swallowed.		
Data for PLEXIGLAS® DR	®-101 ACRYLIC RE			
Acute T	Acute Toxicity			
	Dermal: Acute toxicity estimate > 5,000 mg/kg			
Inhala	Inhalation: 4 h Acute toxicity estimate > 10 mg/L			

# Data for Acrylic copolymers (Proprietary)

## Other Information

The information presented is from representative materials in this chemical class. The results may vary depending on the test substance. Effects due to processing releases or residual monomer: Possible cross sensitization with other acrylates and methacrylates.

## Data for Acrylic styrene copolymers (proprietary)

# Other Information

The information presented is from a representative material with a similar structure. The results vary depending on the size and composition of the test substance.

Effects due to processing releases or residual monomer: Possible cross sensitization with other acrylates and methacrylates.

# Additional Toxicological Information

When used and handled according to specifications, the product does not have any harmful effects according research and information provided by suppliers.

to

# Carcinogenic Effect

International Agency for Research on Cancer (IARC) : Group 3 NOT classifiable as to its carcinogenicity to humans.

Section 12. Ecological Informa	tion
Eco-toxicity:	Toxicity to fish - No relevant studies identified.
Persistence and Degradability:	This material is not expected to be readily biodegradable.
Bio-accumulate Potential:	Product is not likely to accumulate in biological organisms.
Mobility in Soil:	This Product has not been found to migrate through soils.

This Substance is not in Annex I of Regulation (EC) 2037/2000 on substances that deplete the

Other Adverse Effects: ozone layer.

## Section 13. Disposal Considerations

### **Disposal Methods**

Product Recommendation:

- 1. Recycle (Reprocess) if product has not been contaminated so as to make it unsuitable for its intended use.
- 2. Disposal through controlled incineration or authorized waste dump in accordance with Local, State or Federal Regulations.

Uncleaned Packaging Recommendation:

1. Disposal must be done in accordance with Local, State, or Federal Regulation.

# Section 14. Transportation Information

UN Number: Not Relevant
UN Proper Shipping Name: Not Relevant

### Transportation Hazard Class(es)

DOT: Not Regulated/classified
ADR / RID: Not Regulated/classified
Environmental Hazards: Not Relevant

Environmental riazarde.

Transportation in Bulk (According to Annex II of MARPOL 73/78 and IBC Code): Not Relevant

Special Precautions for User: No special precautions

# Section 15. Regulatory Information

The components of this product are all on the TSCA inventory list. (Not meant to be all-inclusive -- select regs represented)

Hazard categories under criteria of SARA Title III Rules (40 CFR Part 370)

Immediate (Acute) Health	N	Delayed (Chronic) Health	N
Sudden Release of Pressure	N	Reactive	N
Fire	N		

# **INGREDIENT RELATED REGULATORY INFORMATION:**

SARA REPORTABLE QUANTITIES	CERCLA RQ	SARA TPQ
Ethyl acrylate	1000 LBS	N/A
Methyl methacrylate	1000 LBS	N/A
P (EA/MMA)	N/A	N/A

# **SARA TITLE III, SECTION 313**

This product does contain chemical(s), which are defined as toxic chemicals under and subject to the reporting requirements of, Section 313 of Title III of the Superfund Amendments and Reauthorization Act of 1986 and 40 CFR Part 372. See section 2.

Chemical Name	CAS-No.	De minimis concentration	Reportable Threshold:
Ethyl acrylate	Not assigned	Not assigned	Not assigned
Methy methacrylate	Not assigned	Not assigned	Not assigned
Aluminium	Not assigned	Not assigned	Not assigned
Copper	Not assigned	Not assigned	Not assigned
2-Propenoic acid, ethyl ester	140-88-5	0.10%	10000 lbs (otherwise used (non-manufacturing/processing)) 25000 lbs (manufacturing and processing)

# Comprehensive Environmental Response, Compensation, and Liability Act (CERCLA)-Reportable Quantity (RQ)

Chemical Name	CAS-No.	Reportable quantity
2-Propenoic acid, 2-methyl-, methyl ester	80-62-6	1000 lbs
2-Propenoic acid, ethyl ester	140-88-5	1000 lbs

## **Chemical Inventory Status**

EU. EINECS	EINECS	Conforms to
		The components of this product are all
United States TSCA Inventory	TSCA	on the TSCA Inventory

Canadian Domestic Substnaces List (DSL)	DSL	All components of this product are on the Canadian DSL.
China. Inventory of Existing Chemical Substances in China (IECSC)	IECSC (CN)	Does not conform
Japan. ENCS - Existing and New Chemical Substances Inventory	ENCS (JP)	Does not conform
Japan. ISHL-Inventory of Chemical Substances	ISHL (JP)	Does not conform
Korea. Korean Existing Chemicals Inventory	KECI (KR)	Conforms to
Philippines Inventory of Chemicals and Chemical Substances (PICCS)	PICCS (PH)	Conforms to
Australia Inventory of Chemical Substances	AICS	Conforms to

### State Right-to-Know Information

The following chemicals are specifically listed by individual states; other product specific data in other sections of the SDS may also be applicable for state requirements. For details on your regulatory requirements you should contact the appropriate agency in your state.



## WARNING:

This product can expose you to chemicals including styrene, which is known to the State of California to cause cancer. For more information go to www.P65Warnings.ca.gov

#### Other Information Section 16.

The information presented in this Safety Data Sheet is based on data considered to be accurate as of the date this Safety Data Sheet was prepared. However, no warranty or representation, expressed or implied, is made as to the accuracy or completeness of the foregoing data and safety information, nor is any authorization given or implied to practice any patented invention without a license. In additional, no responsibility can be assumed by vendor for any damage or injury resulting from abnormal use, from any failure to adhere to recommended practices, or from any hazards inherent in the nature of the product.

Revision Date: January 2020

OSHA HazCom:	This Material i	s not Hazardous b OSHA Hazard	dous Communication Standard 29 CFR 1910.1200
SARA 313:			
Immediate Hazard:	NO	Fire Hazard: NO	Reactivity Hazard: NO
Delayed Hazard: NC	)	Pressure Hazard: NO	

# Section 16. Other Information

No Additional Information

**NOTICE:** The information presented in this Safety Data Sheet is based on data considered to be accurate as of the date this Safety Data Sheet was prepared. However, no warranty or representation, expressed or implied, is made as to the accuracy or completeness of the foregoing data and safety information, nor is any authorization given or implied to practice any patented invention without a license. In additional, no responsibility can be assumed by vendor for any damage or injury resulting from abnormal use, from any failure to adhere to recommended practices, or from any hazards inherent in the nature of the product.

|--|