



SAFETY DATA SHEET

SDS No: 0011

Section 1. Product and Company Identification

Product Name: Hardwood Collection (wood)

Trade Name: Wood Dust (Untreated)

Recommended Use: Signage, Other

Restrictions on Use: None

Manufacture: Rowmark
5409 Hamlet Drive
Findlay, OH 45840

In Case of Emergency: Call: Medical: 911
Poison Control: 800-589-3897
Information: Call: 1-877-ROWMARK
Email: techhelp@rowmark.com

Section 2. Hazard Identification

GHS Classification: Not Classified

GHS Label Elements: Not Applicable

Potential Health Effects:

EYE: Solid or dust may cause irritation or corneal injury due to mechanical action.

INHALATION: Dust may cause irritation to upper respiratory tract (nose and throat).

INGESTION: Very low toxicity if swallowed. Harmful effects not anticipated from swallowing small amounts.

SKIN: Essentially non-irritating to the skin. Mechanical injury only. If heated, contact with the material may cause thermal burns. No adverse effects anticipated by skin absorption.

GHS Rating

Health	5
Flammability	4
Instability	5
Other	

Other Hazards: Not Applicable

NEW GHS Hazard Categories

Category 1 = Severe Hazard

Category 2 = Serious Hazard

Category 3 = Moderate Hazard

Category 4 = Slight Hazard

Category 5 = Minimal Hazard

Section 3. Composition / Information on Ingredients

Name	CAS #	% by Weight
Wood Dust	N/A	90-100%

* Remaining components are proprietary, non-hazardous, and/or present at amounts below reportable limits.

Section 4. First Aid Measures

Inhalation: Dust and process vapors may be irritation to the nose, throat and respiratory tract. Remove to fresh air. If not breathing, give artificial respiration. If breathing is difficult, give oxygen. Get Medical attention.

Eyes: Dust, fines and process vapors may irritate the eyes. Immediately flush eyes with water for at least 15 minutes. Get medical attention.

Skin: Wash affected areas with soap and water. Get medical advice if rash or persistent irritation or dermatitis occurs.

Ingestion: No adverse health effects expected from ingestion.

Section 5. Fire-Fighting Measures

Suitable Extinguishing Methods: Dry Chemical, Water Spray, Foam Carbon Dioxide, Sand

Unsuitable Extinguishing Methods: None known.

Hazards During Fire-fighting: Carbon monoxide, carbon dioxide, original monomer other hydrocarbon oxidation products.

Protective Equipment: Wear self-contained breathing apparatus and protective suit.

Section 6. Accidental Release Measures

Personal Precautions: See Section 8 - Exposure Controls / Personal Protection.

Environmental Precautions: No Special environmental precautions required.

Methods and Materials for Containment and Cleaning Up

Spill / Leak: Containment of this material should not be necessary. Sweep up or gather material and place in

If Molten: Allow material to cool and place into an appropriate marked container for disposal.

Section 7. Handling and Storage

Handling: Keep away from heat, flame and strong oxidizing agents. Good housekeeping and controlling dusts are necessary for safe handling of product. Workers should be protected from the possibility of contact with molten resin during fabrication. Large masses of molten polymer held at elevated temperatures for extended periods of time may auto-ignite.

Storage: Keep away from heat, sparks, and flame. Store horizontally in cool, dry place in original container and protect from sunlight.

Section 8. Exposure Control and Personal Protection**Exposure Limits:**

1) **Effects of Acute Exposure:** See section 11, Toxicological Information

2) **Effects of Chronic Over Exposure:** See section 11, Toxicological Information

3) Permissible Exposure Limits:	Chemical	OSHA PEL	ACGIH TLV
	Formaldehyde	0.75 ppm TWA 2 ppm STEL	Ceiling: 0.3 ppm
	Wood Dust	5.0 mg/m ³ (total dust) TWA	Not Assigned
	Wood Dust (softwood)	Not Assigned	5.0 mg/m ³ TWA 10.0 mg/m ³ (15 min) STEL
	Wood Dust (certain hardwoods such as beach and oak)	Not Assigned	1.0 mg/m ³ TWA

4) **Carcinogen Potential:** See section 11, Toxicological Information

Engineering Controls:

Use recommended safe handling practices to minimize unnecessary exposure.

General room ventilation is adequate for storage and ordinary handling.

Use local exhaust at points of fume generation or if dusty conditions prevail.

Personal Protective Equipment:

Wear safety glasses with side shields or chemical goggles to prevent eye contact.

Have eye-washing facilities readily available where eye contact can occur.

Wear impervious gloves and protective clothing to prevent skin contact.

Section 9. Physical and Chemical Properties

characteristic odor	Various color	Vapor Pressure:	Not applicable
Odor:	Various odors	Vapor Density:	Not applicable
pH:	Not applicable	Relative Density:	<1
Melting Point / Freezing Point:	Not applicable	Solubility (ies):	Insoluble in water
Boiling Point:	Not Applicable	Partition Coefficient (N-Octanol/Water):	Not applicable
Flash Point:	Not Applicable	Auto-Ignition Temperature:	Variable, typically 400-500°F
Evaporation Rate:	Not Applicable	Decomposition Temperature:	Not applicable
Flammability (solid, gas):	Dust and solid are flammable	Viscosity:	Not applicable
Upper Explosive Limit:	Not established	Specific Gravity:	<1
Lower Explosive Limit:	40 grams/m ³	Percent Volatile:	0

Section 10. Stability Reactivity

Reactivity: Stable

Chemical Stability: Stable

Possibility of Hazardous Reactions: None known

Conditions to Avoid: Avoid contact with oxidizing agents. Avoid open flames and temperatures over 400°F

Incompatible Materials: None known

Hazardous Decomposition Products: Thermal decomposition can produce irritating and toxic fumes and gases, including carbon monoxide, hydrogen cyanide, aldehydes, organic acids and polynuclear aromatic compounds.

Section 11. Toxicological Information**Irritation Effects**

Eye Irritation: Solid particles may cause transient irritation from mechanical abrasion.

Skin Irritation: Not expected to cause skin irritation. Molten material may cause thermal burns.

Inhalation: Not a likely route of exposure. Process fumes may cause irritation.

Ingestion: May cause a choking hazard if swallowed.

Accute Effects of Exposure: Gases and fumes evolved during thermal processing or decomposition of this material may irritate the eyes, skin or respiratory tract and cause nausea, drowsiness and headache.

Chronic (non-cancer) Effects of Exposure: Not expected to cause any adverse chronic health effects.

Carcinogenicity:

Formaldehyde is listed by the International Agency for Research on Cancer as a probable human carcinogen. The National Toxicology Program includes formaldehyde in the Annual Report on Carcinogens. Formaldehyde is regulated by OSHA as a potential cancer agent.

Section 12. Ecological Information

Eco-toxicity:	No relevant studies identified.
Persistence and Degradability:	Biodegradable
Bio-accumulate Potential:	Product is not likely to accumulate in biological organisms.
Mobility in Soil:	This Product has not been found to migrate through soils.
Other Adverse Effects:	Not Assigned

Section 13. Disposal Considerations

Disposal Methods

Product Recommendation:

1. Recycle (Reprocess) if product has not been contaminated so as to make it unsuitable for its intended use.
2. Disposal through controlled incineration or authorized waste dump in accordance with Local, State or Federal Regulations.

Uncleaned Packaging Recommendation:

1. Disposal must be done in accordance with Local, State, or Federal Regulation.

Section 14. Transportation Information

UN Number:	Not Relevant
UN Proper Shipping Name:	Not Relevant

Transportation Hazard Class(es)

DOT:	Not Regulated/classified
TDG:	Not Regulated/classified
ADR / RID:	Not Regulated/classified
IMDG:	Not Regulated/classified
ICAO/IATA	Not Regulated/classified
Packing Group:	Not Applicable
Environmental Hazards:	Not Relevant
Transportation in Bulk (According to Annex II of MARPOL 73/78 and IBC Code):	Not Relevant
Special Precautions for User:	No special precautions

Section 15. Regulatory Information

NOTICE: The information herein is presented in good faith and believed to be accurate as of the effective date shown above. However, no warranty, express or implied is given. Regulatory requirements are subject to change and may differ from one location to another; it is the buyer's responsibility to ensure that its activities comply with federal, state or provincial, and local laws. The following specific information is made for the purpose of complying with numerous federal, state or provincial, and local laws and regulations. See other sections for health and safety information. Not intended to be all-inclusive.

US EPA Resource Conservation and Recovery Act (RCRA) Composite List of Hazardous Wastes and Appendix VIII

If discarded in purchased form, this product would not be a hazardous waste either by listing or by characteristic. However, under RCRA, it is the responsibility of the product user to determine at the time of disposal, whether a material containing the product or derived from the product should be classified as a hazardous waste (40 CFR 261.20-24).

OSHA HazCom: This Material is not Hazardous OSHA Hazardous Communication Standard 29 CFR 1910.1200

SARA 313:

Immediate Hazard: NO	Fire Hazard: NO	Reactivity Hazard: NO
Delayed Hazard: NO	Pressure Hazard: NO	

⚠ WARNING:
This product can expose you to chemicals including styrene, which is known to the State of California to cause cancer.
For more information go to www.P65Warnings.ca.gov

Section 16. Other Information

The information presented in this Safety Data Sheet is based on data considered to be accurate as of the date this Safety Data Sheet was prepared. However, no warranty or representation, expressed or implied, is made as to the accuracy or completeness of the foregoing data and safety information, nor is any authorization given or implied to practice any patented invention without a license. In addition, no responsibility can be assumed by vendor for any damage or injury resulting from abnormal use, from any failure to adhere to recommended practices, or from any hazards inherent in the nature of the product.

Revision Date: January 2020
