

## Material Information Sheet

### Material Description: ColorHues™ Glitter

| Specifications        |                                          |
|-----------------------|------------------------------------------|
| Material:             | Cell Cast Acrylic                        |
| Finish:               | Matte   Gloss                            |
| Sheet Size:           | 24"x 48 3/4" (610 x 1238 mm)             |
| Thickness: Single Ply | 1/8" (3.2mm)<br>1/4" (6.4mm)             |
| Usage:                | Architectural Signage   Corporate Awards |
| Engraving Method:     | CO2 Laser                                |

| Physical Properties                                              | Typical Values                  | ASTM Method |
|------------------------------------------------------------------|---------------------------------|-------------|
| <b>Flexural Strength</b>                                         |                                 |             |
| Load to stretch outer surface 5%                                 | 1050kg/cm squared               | D-790       |
| <b>Electrical – Arc Resistance</b>                               | 10 <sup>12</sup> Ohms/Sq. Meter | D-495       |
| <b>Rockwell Hardness</b>                                         | M45                             | D-785       |
| <b>Specific Gravity</b>                                          | 1.19 – 1.20                     | D-792       |
| <b>Deflection Temperature</b>                                    |                                 |             |
| Temperature at which material deflects .010" (.254mm) at 264 psi | 212°F (100°C)                   | D-648       |
| <b>Coefficient of Thermal Expansion</b>                          |                                 |             |
| Inch/inch/°F                                                     | 6x10 <sup>-5</sup> /cm/°C       | D-696       |

**ColorHues™ Glitter** material softens sufficiently at approx. 180°F (82.22°C), which enables bending, should that be desired. It can also be drilled, sawed, sheared, and bonded to itself or other materials. Cast acrylics have thickness variations that may present difficulties in applications where thickness tolerance is important (i.e. fitting into extrusion, thermoforming application where walls must maintain uniform thickness and assembly of complex structures.) Remember to check gauge when non-contact engraving takes place and to periodically re-check focal lengths when laser engraving. In some cases, thickness variations may require the operator to make multiple passes during laser engraving.

Electrically non-conductive, Insulative. Meets 10<sup>12</sup> Ohms/square meter or higher in electrical resistivity, RoHS compliant (halogen-free), PVC-free, Formaldehyde and Phenol free, clean room compliant and rated UL 94 HB. Material was judged as not contributing to the combustion of the base material.

### Terms & Condition of Sale

Rowmark warranty is limited to replacement of product only, and such warranty does not extend to the costs of any repeat labor or incidental costs. *LIMITED WARRANTY, WARRANTY DISCLAIMERS AND LIMITATIONS OF REMEDIES AND LIABILITIES:* Except as set forth above, Seller makes *NO OTHER WARRANTIES* concerning the products whatsoever.

**Note:** The above information is given in good faith, but no warranty, express or implied, is given.