

Material Information Sheet

Material Description: Satins

Specifications		
Material:	Acrylic Cap ABS (Acrylonitrile Butadiene Styrene) Core	
Finish:	Brushed	
Sheet Size:	24"x 48 3/4" (610 x 1238mm)	
Thickness: 2-Ply and 3-Ply	1/32" (0.8mm) 3/32" (.24mm) 1/16" (1.6mm) 1/8" (3.2mm)	
Usage:	Interior Signage Personal Identification	
Engraving Method:	Rotating carbide	
Engraving Depth:	.012" / 0.30mm	
Physical Properties		
<u>IZOD Impact Strength</u>		
Notched at 73°F (22.78°C)	2 ft lbs/in	D-256
<u>Tensile Strength</u>		
To break	7,000 psi	D-638
Elongation before break	28%	D-638
<u>Flexural Strength</u>		
Loan to stretch outer surface 5%	11,000 psi	D-790
<u>Electrical – Arc Resistance</u>	10^12 Ohms/Sq. Meter	D-495
<u>Rockwell Hardness</u>	M45	D-785
<u>Specific Gravity</u>	1.15	D-792
<u>Deflection Temperature</u>		
Temperature at which material deflects .010" (.254mm) at 264 psi	186°F (79.44°C)	D-648
<u>Coefficient of Thermal Expansion</u>		
Inch/inch/°F	5.0 x 10 ⁻⁵	D-696
<u>Vicat Softening Point</u>		
Temperature for needle to penetrate 1mm (90°F/hr, 2.2 lbs)	217°F (97.78°C)	D-1525
Satins material softens sufficiently at about 180°F (82.22°C), which enables bending, should that be desired. It can also be drilled, sawed, sheared, and bonded to itself or other materials.		

Electrically non-conductive, Insulative, Fire retardant, Non-flammable. Meets 10¹² Ohms/square meter or higher in electrical resistivity, RoHS compliant (halogen-free), PVC-free, Formaldehyde and Phenol free and UL 94 V0. Material was judged as not contributing to the combustion of the base material.

Terms & Condition of Sale

Rowmark warranty is limited to replacement of product only, and such warranty does not extend to the costs of any repeat labor or incidental costs. **LIMITED WARRANTY, WARRANTY DISCLAIMERS AND LIMITATIONS OF REMEDIES AND LIABILITIES:** Except as set forth above, Seller makes **NO OTHER WARRANTIES** concerning the products whatsoever.

Note: The above information is given in good faith, but no warranty, express or implied, is given.

PO Box 1605
5409 Hamlet Drive
Findlay, Ohio 45839-1605
P 419.425.8974
F 419.425.0501

rowmark.com

Last Updated: April 10, 2026