

# SAFETY DATA SHEET

SDS No: 0014

Section 1. **Product and Company Identification** 

Product Name: LaserGlow™

Impact Modified Acrylic Trade Name: Recommended Use: Signage, Other

Restrictions on Use: None

Manufacture: Rowmark

> 5409 Hamlet Drive Findlay, OH 45840

In Case of Emergency: Call: Medical: 911

Poison Control: 800-589-3897

Information: Call: 1-877-ROWMARK

Email: techhelp@rowmark.com

**NEW GHS Hazard Categories** Category 1 = Severe Hazard

Category 2 = Serious Hazard Category 3 = Moderate Hazard

Category 4 = Slight Hazard Category 5 = Minimal Hazard

#### Section 2. **Hazard Identification**

GHS Classification: Not Classified GHS Label Elements: Not Applicable

## **GHS Rating**

Health	5
Flammability	4
Instability	5
Special	

Instability	5			
Special				
Other Hazards:	Not A	pplicable		
Section 3.	Composit	ion / Information on Inເ	gredients	
1	Name	CAS#	% by Weight	OHSA
P (E	EA/MMA)	Proprietary	50-54	N

Acrylic Styrene Copolymer Proprietary 35-50 Ν Green Photoluminescent Proprietary 18-25 Ν Methyl methacrylate 80-62-6 < 0.5 Υ 140-88-5 < 0.1 Ethyl acrylate

The substance(s) marked with a "Y" in the OSHA column are idenfitied as hazardous chemicals according to the criteria of the OSHA Hazardous Communication Standard (29 CFR 1910.1200).

While this material is not classified as hazardous under Federal OSHA regulations, this SDS contains valuable information critical to the safe handling and proper use of this product. This SDS should be retained and available for employees and other users of this product. The components of this product are all on the TSCA Inventory list.

The components of this product are all on the TSCA Inventory list. Remaining components are proprietary, non-hazardous, and/or present at amounts below reportable limits.

Section 4.	First Aid Measures
Inhalation:	Dust and process vapors may be irritation to the nose, throat and respiratory tract. Remove to fresh air. If not
	breathing, give artificial respiration. If breathing is difficult, give oxygen. Get Medical attention.
Eyes:	Dust, fines and process vapors may irritate the eyes. Immediately flush eyes with water for at least 15
Lусо.	minutes. Get medical attention.
Skin:	Exposure to molten plastic may cause thermal burns. If molten material comes in contact with the skin, cool
SKIII.	under ice water or a running stream.
Ingestion:	No adverse health effects expected from ingestion.
04! 5	Fig. Fig. Co.
Section 5.	Fire-Fighting Measures

Section 5. Fire-Fighting Me	easures
Suitable Extinguishing Methods:	Dry Chemical, Water Spray, Foam Carbon Dioxide. Avoid using direct streams of water on molten burning material.
Unsuitable Extinguishing Methods:	NONE known.
Hazards During Fire-fighting:  Carbon monoxide, carbon dioxide, original monomer other hydrocarbon oxidation products.	
Protective Equipment:	Wear self-contained breathing apparatus and protective suit.

0 (1 0	A 11 (15 )			
Section 6.	Accidental Relea			
Personal Preca			sure Controls / Personal Protection	on.
Environmental F			ental precautions required.	
Methods and N		ment and Cleaning Up		
Spill / Leak:	appropriate co	ontainer for disposal.	not be necessary. Sweep up or g	jatner material and place in
Section 7.	Handling and Sto			
Handling:		om heat, flame and stro		
Storage:	Keep away fro sunlight.	om heat, sparks, and fl	ame. Store in cool place in origin	al container and protect form
Section 8.		ol and Personal Pro	tection	
Exposure Limi		1110		
	Acute Exposure:	Inhalation of vapors r	nay result in irritation of upper res	spiratory tract
,	Chronic Exposure:		110 A0015 TI	()()
3) OSHA Pern	nissible Exposure Lii		US. ACGIF Threshold Limi	
			Form: ighted average	Inhalable particles 10 mg/m3
			Form:	Respirable particles
		Time we	ighted average	3 mg/m3
			Table Z-1 Limits for Air Contamir	nants (29 CFR 1910.1000)
			Form:	Respirable fraction
			PEL:	5 mg/m3
			Form:	Total dust
			PEL:	15 mg/m3
	US. OSHA Tab	ole Z-3 (29 CFR 1910.1	1000)	
			Form:	Respirable fraction
		Time we	ighted average	15 ppm
			Form:	Total dust
		Time we	ighted average	50 ppm
			F	Respirable fraction
			Form: ighted average	5 mg/m3
			Form:	Total dust
			ighted average	15 mg/m3
4) Carcinoger				
Engineering Co		anda handling of the	to mainimaine	
		• • • • • • • • • • • • • • • • • • • •	s to minimize unnecessary exposi	ле.
			torage and ordinary handling.	
Personal Prote	Use local exhaust at ective Equipment:	t points of fume genera	ation or if dusty conditions prevail.	
	Wear safety glasses	s with side shields or c	hemical goggles to prevent eye co	ontact.
	Have eye-washing f	acilities readily availab	le where eye contact can occur.	
	Wear impervious glo	oves and protective clo	thing to prevent skin contact.	
Section 9.	Physical and Che	emical Properties		
Appearance:		Various Colors	Vapor Pressure:	Not Applicable
Odor:		Slightly acrylic	Vapor Density:	Not Applicable
pH:		Not applicable	Relative Density:	1.19 g/cm3
Melting Point / F	reezing Point:	No data available	Solubility (ies):	Not Applicable
Boiling Point:		No data available	Partition Coefficient (N-Octanol/\	V <sub>έ</sub> No data available
Flash Point:		Not applicable	Auto-Ignition Temperature:	739°F (393°C)
Evaporation Ra	te:	Not applicable	Decomposition Temperature:	>572°F (> 300°C)
Flammability (so	olid, gas):	See GHS in section 2	Viscosity:	No data available
	1.1. 14	A. 1. 1. 1.1	0 15 0 1	4 40 10/1 4 (1: :1)

Upper Explosive Limit:

Not applicable

Specific Gravity:

1.19 Water = 1 (liquid)

Lower Explosive Limit:	Not applicable	Percent Volatile:	0%

Section 10. Stability Reactive	ty
Reactivity:	No data available
Chemical Stability:	Stable
Possibility of Hazardous Reactions:	Hazardous polymerization does not occur
Conditions to Avoid:	Avoid flames, welding arcs, potential ignition sources, or other high temperature sources, prolonged contact with acids, alkalis and strong oxidizing agents
Incompatible Materials:	None under normal conditions of use
Hazardous Decomposition Products:	Carbon oxides, Acrylates, Methacrylates, Hazardous organic compounds
Combustion Products:	No data available

# Section 11. Toxicological Information

#### **Irritation Effects**

Eye Irritation:	Solid particles may cause transient irritation from mechanical abrasion.
Skin Irritation:	Not expected to cause skin irritation. Molten material may cause thermal burns.
Inhalation:	Not a likely route of exposure. Process fumes may cause irritation.
Ingestion:	May cause a choking hazard if swallowed.

#### Data for PLEXIGLAS® DR®-101 ACRYLIC RES

## **Acute Toxicity**

Dermal: Acute toxicity estimate > 5,000 mg/kg Inhalation: 4 h Acute toxicity estimate > 10 mg/L

## **Data for Acrylic copolymers (Proprietary)**

## **Other Information**

The information presented is from representative materials in this chemical class. The results may vary depending on the test substance.

Effects due to processing releases or residual monomer: Possible cross sensitization with other acrylates and methacrylates.

# Data for Acrylic styrene copolymers (proprietary)

# Other Information

The information presented is from a representative material with a similar structure. The results vary depending on the size and composition of the test substance.

Effects due to processing releases or residual monomer: Possible cross sensitization with other acrylates and methacrylates.

## **Additional Toxicological Information**

When used and handled according to specifications, the product does not have any harmful effects according to research and information provided by suppliers.

## **Carcinogenic Effect**

International Agency for Research on Cancer (IARC): Group3 NOT classifiable as to its carcinogenicity to humans.

Section 12. Ecological Infor	mation
Eco-toxicity:	Toxicity to fish - No relevant studies identified.
Persistence and Degradability:	This material is not expected to be readily biodegradable.
Bio-accumulate Potential:	Product is not likely to accumulate in biological organisms.
Mobility in Soil:	This Product has not been found to migrate through soils.
	This Substance is not in Annex I of Regulation (EC) 2037/2000 on substances that
Other Adverse Effects:	deplete the ozone layer.

## Section 13. Disposal Considerations

#### **Disposal Methods**

Product Recommendation:

- 1. Recycle (Reprocess) if product has not been contaminated so as to make it unsuitable for its intended use.
- 2. Disposal through controlled incineration or authorized waste dump in accordance with Local, State or Federal Regulations.

Uncleaned Packaging Recommendation:

1. Disposal must be done in accordance with Local, State, or Federal Regulation.

Section 14.	Transportation Ir	nformation	
UN Number:		Not Relevant	
UN Proper Shipp	ing Name:	Not Relevant	
Transportation	Hazard Class(es)		

DOT: Not Regulated/classified
ADR / RID: Not Regulated/classified
IMDG: Not Regulated/classified
ICAO/IATA Not Regulated/classified

Packing Group: Not Applicable
Environmental Hazards: Not Relevant

Transportation in Bulk (According to Annex II of MARPOL 73/78 and IBC Code): Not Relevant

Special Precautions for User: No special precautions

# Section 15. Regulatory Information

(Not meant to be all-inclusive -- selected regulations represented)

Hazard categories under criteria of SARA Title III Rules (40 CFR Part 370)

Immediate (Acute) Health	N	Delayed (Chronic) Health	N
Sudden Release of Pressure	N	Reactive	N
Fire	N		

The components of this product are all on the TSCA inventory list.

#### INGREDIENT RELATED REGULATORY INFORMATION:

SARA REPORTABLE QUANTITIES	CERCLA RQ	SARA TPQ
Ethyl acrylate	1000 LBS	N/A
Methyl methacrylate	1000 LBS	N/A
P (EA/MMA)	N/A	N/A

# **SARA TITLE III, SECTION 313**

This product does contain chemical(s), which are defined as toxic chemicals under and subject to the reporting requirements of, Section 313 of Title III of the Superfund Amendments and Reauthorization Act of 1986 and 40 CFR Part 372. See section 2.

Chemical Name	CAS-No.	De minimis concentration	Reportable Threshold:
Ethyl acrylate	Not assigned	Not assigned	Not assigned
Methy methacrylate	Not assigned	Not assigned	Not assigned
2-Propenoic acid, ethyl ester	140-88-5	0.10%	10000 lbs (otherwise used (non- manufacturing/processing)) 25000 lbs (manufacturing and processing)

## Comprehensive Environmental Response, Compensation, and Liability Act (CERCLA)-Reportable Quantity (RQ)

Chemical Name	CAS-No.	Reportable quantity
2-Propenoic acid, 2-methyl-, methyl ester	80-62-6	1000 lbs
2-Propenoic acid, ethyl ester	140-88-5	1000 lbs

## **Chemical Inventory Status**

EU. EINECS	EINECS	Conforms to	
United States TSCA Inventory	TSCA	The components of this product are all on the TSCA Inventory	
Canadian Domestic Substnaces List (DSL)	DSL	All components of this product are on the Canadian DSL.	
China. Inventory of Existing Chemical Substances in China (IECSC)	IECSC (CN)	Does not conform	
Japan. ENCS - Existing and New Chemical Substances Inventory	ENCS (JP)	Does not conform	
Japan. ISHL-Inventory of Chemical Substances	ISHL (JP)	Does not conform	
Korea. Korean Existing Chemicals Inventory	KECI (KR)	Conforms to	
Australia Inventory of Chemical Substances	AICS	Conforms to	

OSHA HazCom:	This Material is not Hazardous b OSHA Hazardous Communication Standard 29 CFR 1910.1200

SARA 313:

Immediate Hazard: NO	Fire Hazard: NO	Reactivity Hazard: NO
Delayed Hazard: NO	Pressure Hazard: NO	

# **WARNING:**

This product can expose you to chemicals including styrene, which is known to the State of California to cause cancer.

For more information go to www.P65Warnings.ca.gov

# Section 16. Other Information

The information presented in this Safety Data Sheet is based on data considered to be accurate as of the date this Safety Data Sheet was prepared. However, no warranty or representation, expressed or implied, is made as to the accuracy or completeness of the foregoing data and safety information, nor is any authorization given or implied to practice any patented invention without a license. In additional, no responsibility can be assumed by vendor for any damage or injury resulting from abnormal use, from any failure to adhere to recommended practices, or from any hazards inherent in the nature of the product.

Revision Date: January 2020