



SDS No: 0018

Section 1. Product and Company Identification

Product Name: LaserMax®

Trade Name: Film-stamped Impact Modified Acrylic

Recommended Use: Signage, Other

Restrictions on Use: None

Manufacture: Rowmark

5409 Hamlet Drive Findlay, OH 45840 Medical:911

In Case of Emergency: Call: Poison Control: 800-589-3897

Email:

**Information:** Call: 1-877-ROWMARK

Email: techhelp@rowmark.com

## Section 2. Hazard Identification

GHS Classification: Not Classified GHS Label Elements: Not Applicable

**NEW GHS Hazard Categories** 

Category 1 = Severe Hazard
Category 2 = Serious Hazard

Category 3 = Moderate Hazard

Category 4 = Slight Hazard Category 5 = Minimal Hazard

GHS Rating

Health	5
Flammability	4
Instability	5
Special	

Other Hazards: Not Applicable

Other Hazards: Not App	licable		
Section 3. Composition	n / Information on Ingredient	ts	
Name	CAS#	% by Weight	OHSA
P (EA/MMA)	Proprietary	50-54	N
Acrylic Styrene Copolyme	r Proprietary	35-50	N
Methyl methacrylate	80-62-6	< 0.5	Υ
Ethyl acrylate	140-88-5	< 0.1	Y
Aluminium Flake	7429-90-5	1-5	
Carbon Black	1333-86-4	1-5	
Copper	7440-50-8	1-2	

The substance(s) marked with a "Y" in the OSHA column are idenfitied as hazardous chemicals according to the criteria of the OSHA Hazardous Communication Standard (29 CFR 1910.1200).

While this material is not classified as hazardous under Federal OSHA regulations, this SDS contains valuable information critical to the safe handling and proper use of this product. This SDS should be retained and available for employees and other users of this product.

The components of this product are all on the TSCA Inventory list. Remaining components are proprietary, non-hazardous, and/or present at amounts below reportable limits.

Section 4.	First Aid Measures	
Inhalation	Dust and process vapors may be irritation to the nose, throat and respiratory tract. Remove to fresh air. If not	
Inhalation: breathing, give artificial respiration. If breathing is difficult, give oxygen. Get Medical attention.		
Dust, fines and process vapors may irritate the eyes. Immediately flush eyes with water for at least		
Eyes:	Get medical attention.	
Skin:	Exposure to molten plastic may cause thermal burns. If molten material comes in contact with the skin, cool	
SKIII.	under ice water or a running stream.	
Ingestion:	No adverse health effects expected from ingestion.	

Section 5. Fire-Fighting Mo	easures
Suitable Extinguishing Methods:	Dry Chemical, Water Spray, Foam Carbon Dioxide. Avoid using direct streams of water on molten burning material.
Unsuitable Extinguishing Methods:	NONE known.
Hazards During Fire-fighting:	Carbon monoxide, carbon dioxide, original monomer other hydrocarbon oxidation products.

Melting Point / Freezing Point:

Boiling Point:

Section 6.	Accidental Release Measu	ıres		
	Personal Precautions: See Section 8 - Exposure Controls / Personal Protection.			
Environmental F	Environmental Precautions: No Special environmental precautions required.			
Methods and M	Methods and Materials for Containment and Cleaning Up			
Spill / Leak:	Containment of this mate appropriate container for		ot be necessary. Sweep up o	or gather material and place in
Section 7.	Handling and Storage	•		
Handling:	Keep away from heat, fla	ame and stror	ng oxidizing agents.	
Storage:	Keep away from heat, sp sunlight.	oarks, and fla	me. Store in cool place in ori	ginal container and protect form
Section 8.	Exposure Control and Per	sonal Prote	ection	
<b>Exposure Limit</b>	•			
		of vapors ma	ay result in irritation of upper	respiratory tract
2) Effects of C	hronic Exposure:			
3) OSHA Perm	issible Exposure Lin		US. ACGIF Threshold L	imit Values
•	-	F	orm:	Inhalable particles
		Time weig	ghted average	10 mg/m3
		F	form:	Respirable particles
		Time weig	ghted average	3 mg/m3
		US. OSHA 1	able Z-1 Limits for Air Conta	minants (29 CFR 1910.1000)
		F	orm:	Respirable fraction
		1	PEL:	5 mg/m3
			form:	Total dust
		l	PEL:	15 mg/m3
			US. OSHA Table Z-3 (29 C	•
		_	orm:	Respirable fraction
		Time weig	ghted average	15 ppm
		F	orm:	Total dust
			ghted average	50 ppm
		`	,	
			orm:	Respirable fraction
		Time weig	ghted average	5 mg/m3
		-	orm:	Total dust
			ghted average	15 mg/m3
		Time weig		
4) Carcinogen				
Engineering Co			4- maining in a 1111	
	Use recommended safe handli			oosure.
	General room ventilation is add	-		roil
Davagnal Drata	Use local exhaust at points of t	iume general	ion of it dusty conditions prev	/all.
Personal Protec	ctive Equipment:  Wear safety glasses with side	shields or ch	emical goggles to prevent ev	e contact
	Have eye-washing facilities rea			
	Wear impervious gloves and p	-		
Section 0			<u> </u>	
Section 9.	Physical and Chemical Pro	-	Vanar Draggues	Not Applicable
Appearance:	Various C		Vapor Pressure:	Not Applicable
Odor:	Slightly ac	_	Vapor Density:	Not Applicable
pH:	Not applic	capie	Relative Density:	1.19 g/cm3

Solubility (ies):

No data available

No data available

Not Applicable

Partition Coefficient (N-Octanol/W No data available

Flash Point:	Not applicable	Auto-Ignition Temperature:	739°F (393°C)
Evaporation Rate:	Not applicable	Decomposition Temperature:	>572°F (> 300°C)
Flammability (solid, gas):	See GHS in section 2	Viscosity:	No data available
Upper Explosive Limit:	Not applicable	Specific Gravity:	1.19 Water = 1 (liquid)
Lower Explosive Limit:	Not applicable	Percent Volatile:	0%

Section 10. Stability Reactiv	ity
Reactivity:	No data available
Chemical Stability:	Stable
Possibility of Hazardous Reactions:	Hazardous polymerization does not occur
Conditions to Avoid:	Avoid flames, welding arcs, potential ignition sources, or other high temperature sources, prolonged contact with acids, alkalis and strong oxidizing agents
Incompatible Materials:	None under normal conditions of use
Hazardous Decomposition Products:	Carbon oxides, Acrylates, Methacrylates, Hazardous organic compounds
Combustion Products:	No data available

# Section 11. Toxicological Information

#### **Irritation Effects**

Eye Irritation:	Solid particles may cause transient irritation from mechanical abrasion.
Skin Irritation:	Not expected to cause skin irritation. Molten material may cause thermal burns.
Inhalation:	Not a likely route of exposure. Process fumes may cause irritation.
Ingestion:	May cause a choking hazard if swallowed.

#### Data for PLEXIGLAS® DR®-101 ACRYLIC RES

#### **Acute Toxicity**

Dermal: Acute toxicity estimate > 5,000 mg/kg
Inhalation: 4 h Acute toxicity estimate > 10 mg/L

# **Data for Acrylic copolymers (Proprietary)**

# **Other Information**

The information presented is from representative materials in this chemical class. The results may vary depending on the test substance.

Effects due to processing releases or residual monomer: Possible cross sensitization with other acrylates and methacrylates.

#### **Data for Acrylic styrene copolymers (proprietary)**

#### **Other Information**

The information presented is from a representative material with a similar structure. The results vary depending on the size and composition of the test substance.

Effects due to processing releases or residual monomer: Possible cross sensitization with other acrylates and methacrylates.

## **Additional Toxicological Information**

When used and handled according to specifications, the product does not have any harmful effects according to research and information provided by suppliers.

# **Carcinogenic Effect**

International Agency for Research on Cancer (IARC): Group3 NOT classifiable as to its carcinogenicity to humans.

Section 12. Ecological Info	rmation
Eco-toxicity:	Toxicity to fish - No relevant studies identified.
Persistence and Degradability:	This material is not expected to be readily biodegradable.
Bio-accumulate Potential:	Product is not likely to accumulate in biological organisms.
Mobility in Soil:	This Product has not been found to migrate through soils.
Other Adverse Effects:	This Substance is not in Annex I of Regulation (EC) 2037/2000 on substances that deplete the ozone layer.

## Section 13. Disposal Considerations

## **Disposal Methods**

Product Recommendation:

- 1. Recycle (Reprocess) if product has not been contaminated so as to make it unsuitable for its intended use.
- 2. Disposal through controlled incineration or authorized waste dump in accordance with Local, State or Federal Laws.

Uncleaned Packaging Recommendation:

1. Disposal must be done in accordance with Local, State, or Federal Regulation.

Section 14. Transportation	n Information	
UN Number:	Not Relevant	
UN Proper Shipping Name:	Not Relevant	
Transportation Hazard Class(es	3)	
DOT:	Not Regulated/classified	
ADR / RID:	Not Regulated/classified	
IMDG:	Not Regulated/classified	
ICAO/IATA	Not Regulated/classified	
Packing Group:	Not Applicable	
Environmental Hazards:	Not Relevant	
Transportation in Bulk (According	to Annex II of MARPOL 73/78 and IBC Code):	Not Relevant
Special Precautions for User:	No special precautions	

# Section 15. Regulatory Information

Hazard categories under criteria of SARA Title III Rules (40 CFR Part 370)

Immediate (Acute) Health	N	Delayed (Chronic) Health	N
Sudden Release of Pressure	N	Reactive	N
Fire	N		

The components of this product are all on the TSCA inventory list.

# **INGREDIENT RELATED REGULATORY INFORMATION:**

SARA REPORTABLE QUANTITIES	CERCLA RQ	SARA TPQ
Ethyl acrylate	1000 LBS	N/A
Methyl methacrylate	1000 LBS	N/A
P (EA/MMA)	N/A	N/A

#### **SARA TITLE III, SECTION 313**

This product does contain chemical(s), which are defined as toxic chemicals under and subject to the reporting requirements of, Section 313 of Title III of the Superfund Amendments and Reauthorization Act of 1986 and 40 CFR Part 372. See section 2.

Chemical Name	CAS-No.	De minimis concentration	Reportable Threshold:
Ethyl acrylate	Not assigned	Not assigned	Not assigned
Methy methacrylate	Not assigned	Not assigned	Not assigned
Aluminium	Not assigned	Not assigned	Not assigned
Copper	Not assigned	Not assigned	Not assigned
2-Propenoic acid, ethyl ester	140-88-5	0.10%	10000 lbs (otherwise used (non-manufacturing/processing)) 25000 lbs (manufacturing and processing)

Comprehensive Environmental Response, Compensation, and Liability Act (CERCLA)-Reportable Quantity (RQ)

Chemical Name	CAS-No.	Reportable quantity
2-Propenoic acid, 2-methyl-, methyl ester	80-62-6	1000 lbs
2-Propenoic acid, ethyl ester	140-88-5	1000 lbs

**Chemical Inventory Status** 

enormous inventory etatas			
EU. EINECS	EINECS	Conforms to	
United States TSCA Inventory	TSCA	The components of this product are all on the TSCA Inventory	
Canadian Domestic Substnaces List (DSL)	DSL	All components of this product are on the Canadian DSL.	
China. Inventory of Existing Chemical Substances in China (IECSC)	IECSC (CN)	Does not conform	
Japan. ENCS - Existing and New Chemical Substances Inventory	ENCS (JP)	Does not conform	

Japan. ISHL-Inventory of Chemical Substances	ISHL (JP)	Does not conform
Korea. Korean Existing Chemicals Inventory	KECI (KR)	Conforms to
Philippines Inventory of Chemicals and Chemical Substances (PICCS)	PICCS (PH)	Conforms to
Australia Inventory of Chemical Substances	AICS	Conforms to

# **WARNING:**

This product can expose you to chemicals including styrene, which is known to the State of California to cause cancer.

For more information go to www.P65Warnings.ca.gov

## Section 16. Other Information

The information presented in this Safety Data Sheet is based on data considered to be accurate as of the date this Safety Data Sheet was prepared. However, no warranty or representation, expressed or implied, is made as to the accuracy or completeness of the foregoing data and safety information, nor is any authorization given or implied to practice any patented invention without a license. In additional, no responsibility can be assumed by vendor for any damage or injury resulting from abnormal use, from any failure to adhere to recommended practices, or from any hazards inherent in the nature of the product.

Revision Date: January 2020

OSHA HazCom:	This Material is not Hazardous b OSHA Hazardous Communication Standard 29 CFR 1910.1200			
SARA 313:				
Immediate Hazard: N	0	Fire Hazard: NO		Reactivity Hazard: NO
Delayed Hazard: NO		Pressure Hazard: NO		

# Section 16. Other Information

No Additional Information

**NOTICE:** The information presented in this Safety Data Sheet is based on data considered to be accurate as of the date this Safety Data Sheet was prepared. However, no warranty or representation, expressed or implied, is made as to the accuracy or completeness of the foregoing data and safety information, nor is any authorization given or implied to practice any patented invention without a license. In additional, no responsibility can be assumed by vendor for any damage or injury resulting from abnormal use, from any failure to adhere to recommended practices, or from any hazards inherent in the nature of the product.

Revision Date: