

Material Information Sheet

Material Description: Satins

Specifications		
Material:	Acrylic Cap ABS (Acrylonitrile Butadiene Styrene) Core	
Finish:	Brushed	
Sheet Size:	24"x 48 3/4" (610 x 1238mm)	
Thickness: 2-Ply and 3-Ply	1/32" (0.8mm) 3/32" (.24mm) 1/16" (1.6mm) 1/8" (3.2mm)	
Usage:	Interior Signage Personal Identification	
Engraving Method:	Rotating carbide	
Engraving Depth:	.012" / 0.30mm	
Physical Properties		
IZOD Impact Strength		
Notched at 73°F (22.78°C)	2 ft lbs/in	D-256
Tensile Strength		
To break	7,000 psi	D-638
Elongation before break	28%	D-638
Flexural Strength		
Load to stretch outer surface 5%	11,000 psi	D-790
Electrical – Arc Resistance	10 ¹² Ohms/Sq. Meter	D-495
Rockwell Hardness	M45	D-785
Specific Gravity	1.15	D-792
Deflection Temperature		
Temperature at which material deflects .010" (.254mm) at 264 psi	186°F (79.44°C)	D-648
Coefficient of Thermal Expansion		
Inch/inch/°F	5.0 x 10 ⁻⁵	D-696
Vicat Softening Point		
Temperature for needle to penetrate 1mm (90°F/hr, 2.2 lbs)	217°F (97.78°C)	D-1525
<p>Satins material softens sufficiently at about 180°F (82.22°C), which enables bending, should that be desired. It can also be drilled, sawed, sheared, and bonded to itself or other materials.</p> <p>Electrically non-conductive, Insulative, Fire retardant, Non-flammable. Meets 10¹² Ohms/square meter or higher in electrical resistivity, RoHS compliant (halogen-free), PVC-free, Formaldehyde and Phenol free and UL 94 V0. Material was judged as not contributing to the combustion of the base material.</p>		
<p>Restriction of Hazardous Substances (RoHS)/ U.L. Certification/Halogenated Materials Rowmark has investigated the Restriction of Hazardous Substances (RoHS 3) directive issued by the European Union (directive 2015/863/EU), through our on-line research. This RoHS directive prohibits the distribution of products after June 2015, which contain the following materials; lead, mercury, cadmium, hexavalent chromium, poly-brominated biphenyls and poly-brominated diphenyl ethers. The directive appears to apply to all products that operate on electrical power and contain electronic components. Rowmark complies with the use and disclosure of all halogenated materials and does not incorporate poly-brominated biphenyls or poly-brominated diphenyl ethers in any of its products. Based on our audit, Rowmark plastic sheet products are in compliance with this directive and do not contain any of the elements noted above or in the candidate list in accordance with the referenced directive. Our related MSDS documents may be found in the Rowmark website (http://www.rowmark.com/MARK/MSDS.asp) and can be referenced for further information.</p>		
<p>Terms & Condition of Sale Rowmark warranty is limited to replacement of product only, and such warranty does not extend to the costs of any repeat labor or incidental costs. <i>LIMITED WARRANTY, WARRANTY DISCLAIMERS AND LIMITATIONS OF REMEDIES AND LIABILITIES:</i> Except as set forth above, Seller makes NO OTHER WARRANTIES concerning the products whatsoever.</p>		
<p><i>Note: The above information is given in good faith, but no warranty, express or implied, is given.</i></p>		